




Alsons Hand Shower Unit Installation Instructions



1. Remove Existing Shower Head

Turn the existing shower head counter-clockwise with adjustable wrench or pliers. Use care not to unscrew the shower arm; hold the shower arm secure. **Note: If your shower arm has a ball on the end of it, it will not work with this shower unit and will need to be replaced with a standard shower arm.**



2. Install Shower Mount/Connect the Hose to Shower Arm Mount

It is recommended to wrap Teflon® Tape (not included) around the threads of the shower arm only. **Hand tighten** the large end of the Shower Arm Mount **clockwise** onto the exposed shower arm threads until tight. Do not use a wrench or pliers.


2A. Standard Installation: A washer, if provided (some of our hoses are washerless), must be firmly seated into the bottom of the standard hex nut end of the Hose. Then firmly **hand tighten** the hose nut **clockwise** onto the Shower Arm Mount outlet. **DO NOT** use a wrench or pliers. **If your Hose has Hose nuts, as pictured in 2A; a vacuum breaker may be required for installation.**

Installation with a Vacuum Breaker: If a Vacuum Breaker is required for your installation, the Vacuum Breaker should be connected to the stand hex nut of the Hose and then attach it to the Shower Arm Mount at the water supply connection. **If you attach the Vacuum Breaker to the Hand Shower, it will not function as desired.**

2B. Vacuum Breaker Hose Installation: Your shower hose is equipped with a Vacuum Breaker, permanently installed in the end of your hose that has a **ridged nut** (as pictured in 2B). **Hand tighten** the ridged nut **clockwise** to the Shower Arm Mount outlet. Do not use a wrench or pliers. **If you attach the ridged nut to the hand shower, the Vacuum Breaker will not function.**

Note: A Vacuum Breaker is a device that is required by certain code authorities to protect your water supply from the back-flow of impure water. The Vacuum Breaker usually **discharges a small amount of water** each time you turn on your shower. It may also **drain water when you shut it off**. Both are normal conditions – the water is draining not leaking.

DO NOT TRY TO REMOVE OR TIGHTEN THE VACUUM BREAKER which is permanently installed into the hose. This could cause damage to the mechanism.



3. Connect Tapered End of Hose to Hand Shower

Seat the washer, if provided, firmly into the hose nut. Remove the yellow tape from the end of the hose that screws onto the hand shower. Carefully align the thread of the **tapered end** of the Hose directly to the Hand Shower. **Hand tighten** - do not use a wrench or pliers. Then place the Hand Shower into the Shower Arm Mount. Rotate the Shower Arm Mount into desired position to hold the Hand Shower.

Lifetime Warranty Alsons Corporation warrants to the owner of this product that the product is free from defects in material or workmanship for the period stated above from the date of purchase. For service in the USA, either return it to the dealer where purchased or return the product, postage prepaid (we recommend United Parcel Service) to Alsons Corporation, 550 Uran Street, Hillsdale, MI 49242. We will repair or replace, at our discretion, at no charge. This warranty gives you specific legal rights. You may also have other rights that vary where you reside. *If this product malfunctions or becomes damaged, stop use and return it to Alsons for examination and/or repair.*

For assistance with problems with installation: In the USA, call toll free 1-800-421-0001, 8:00 a.m. to 6:00 p.m. Eastern Standard Time, Monday - Friday.

If outside USA, write to: Alsons Corporation, 3010 West Mechanic Street, Hillsdale, MI 49242.